



ChemMasters®

Paver Enhancer™

Penetrating Treatment for Pavers
to Enhance Color &
Deepen Appearance

SPECIALTY CONSTRUCTION PRODUCTS

P R O D U C T D A T A

DESCRIPTION

Paver Enhancer is a penetrating, water-based treatment that deepens and enhances the color of architectural, interlocking, porous, dry cast pavers. This product was specifically designed for use on pavers for maximum cosmetic enhancement with excellent breathability. **Paver Enhancer** penetrates the surface of pavers, minimizing the formation of efflorescence and creating a matte finish that resists staining. **Paver Enhancer** is very low in Volatile Organic Compounds (V.O.C.) and compliant in the United States and Canada.

USES

- Exterior pavers to enhance, deepen, and enrich color development
- Enhance and protect the appearance of architectural dry cast pavers

ADVANTAGES

- Penetrating and fully breathable
- Will not contribute to the formation of efflorescence
- Helps maintain original appearance
- Resists staining from oil, grease, food, and beverages
- Protects pavers from water damage
- **Paver Enhancer** is a very low VOC emission product at <100 g/L V.O.C.
- Apply prior to glossy film forming sealers or over penetrating water proofers such as **Certi-Vex PowerSeal SS**

Packaging / Part Number		
4 x 1 gal (3.8L)	36/pallet	F1227.04
5 gal (18.9)	36/pallet	F1227.05

TECHNICAL DATA

Estimating Guide	
Varies with Surface Texture ft ² /gal (m ² /L)	
First coat	200 to 250 (4.9 to 6.1)
Optional 2nd coat	250 to 350 (6.1 to 8.5)

Test Data	
V.O.C.	< 100 g/L
Flash Point °F/°C (closed cup)	>212/100
Weight lbs/gal (kg/L)	8.42 (1.01)

Dry to Condition at 70°F and 50% relative humidity:	
To touch	2 to 4hrs
For foot traffic	4 to 6hrs
For wheeled traffic	24 hrs

DIRECTIONS

Surface Preparation:

- Apply only to non porous dry cast pavers at least 60 days old or to older pavers previously sealed with **Paver Enhancer** or penetrating water proofers such as **Certi-Vex PowerSeal SS**. Age new pavers for 60 days to allow efflorescence to appear before application of **Paver Enhancer**. This is necessary to allow efflorescence removal before sealing in an undesirable appearance.



ChemMasters®

An American Owned & Operated Company

300 EDWARDS STREET • MADISON, OHIO 44057-3112 (440) 428-2105 • FAX (440) 428-7091 • ORDERLINE: (800) 486-7866 www.chemmasters.net

March 2021

- Thoroughly clean pavers using high pressure water and allow pavers to dry completely for at least 24 hours without precipitation, see paver manufacturer's recommendations.
- If efflorescence is present use diluted Muriatic Acid solution per paver supplier's recommendations.
- Always conduct a test application in an inconspicuous area to determine the finished appearance with **Paver Enhancer**.

Mixing: **Paver Enhancer** is packaged ready to use and only requires mild stirring or agitation prior to use. Do not dilute.

Application:

- Use a short nap roller and roller pan or a low pressure air less sprayer equipped with a fan nozzle. Hold sprayer tip 6 to 8 inches (15 to 20cm) from the surface.
- Apply uniformly leaving no pinholes or gaps. Do not allow to pool or puddle.
- An optional second coat may be applied, when surface is dry to foot traffic. To achieve the desired appearance always prepare a test area before applying to entire surface.
- Do not over apply.

Maintenance: Surfaces previously treated with **Paver Enhancer** should be cleaned and re-treated every 1 to 3 years depending on exposure and traffic when pavers no longer exhibit water repellency. Do not over apply.

Cleanup: Before material dries and hardens, clean tools and equipment with warm water and detergent.

Storage: Do not allow to freeze. Store tightly sealed containers in cool, dry area. Shelf life is one year from date of manufacture.

LIMITATIONS:

- **Paver Enhancer** is neither a sealer nor curing compound and should be used exclusively for cosmetic enhancement and improved stain resistance of pavers.
- **Paver Enhancer** is intended for use on new untreated (or previously treated with **Paver Enhancer** or **Certi-Vex PowerSeal SS**) porous dry-cast architectural or interlocking pavers only.
- Do not use if ambient or surface temperature is below 50°F (10°C). For best results, warm material to a minimum of 60°F (15.6°C) prior to application.
- Do not apply if rain is expected within 12 hours of application
- **Paver Enhancer** may highlight uneven color variations in pavers that may be most visible in light gray or beige colored pavers

CAUTIONS

- May cause skin, eye, and respiratory tract irritation.
- All label precautions, warranty, and Safety Data Sheet (SDS) must be fully understood before using this product.
- Make certain that the most current versions of the Product Data Sheet and SDS are being used. Go to www.chemmasters.net or contact ChemMasters Technical Service Department at 1.800.486.7866 to verify the most current version.
- Proper application is the responsibility of the user. ChemMasters can only make technical recommendations and cannot provide quality control on the jobsite. All label directions and the SDS must be understood before beginning application procedure.

Keep out of reach of children

This Product is Formulated and Labeled for Industrial and Commercial Use Only

FOR BEST RESULTS AND SAFEST USAGE, USER IS SPECIFICALLY DIRECTED TO CONSULT THE CURRENT MATERIAL SAFETY DATA SHEET AND PACKAGE LABEL FOR THIS PRODUCT. We warrant our products to meet our published specifications and to be free from defects in materials and workmanship to the acceptable quality levels defined in these specifications. If acceptable quality levels are not specified, the acceptable quality levels will be those normally supplied by us for the product. We make no guarantee of the results to be obtained from the use of our products. The determination as to the adaptability of any of our products to the specific needs of the Buyer is solely Buyer's prerogative and responsibility. We are glad to offer suggestions on the use of our products. Nevertheless, there are no warranties given except such expresses warranties offered in connection with the sale of a particular product. Our liability shall be limited to replacement of, or refund of an amount not to exceed the purchase price attributed to, the goods as to which such claim is made. Our selection of one of these alternatives shall be Buyer's exclusive remedy. IN NO CASE SHALL WE BE LIABLE FOR CONSEQUENTIAL OR SPECIAL DAMAGES, EVEN IF WE HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. THE FOREGOING WARRANTIES ARE IN LIEU OF ALL OTHER WARRANTIES, GUARANTEES, CO-CONDITIONS AND REPRESENTATIONS, EITHER EXPRESSED OR IMPLIED, WHETHER ARISING UNDER ANY STATUTE, COMMON LAW, USAGE OR TRADE, COURSE OF DEALING OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. ©2001 ChemMasters

Printed in U.S.A.