

February 14, 2013

To Whom It May Concern:

<u>Polyseal™ EZ</u> is a single component, solvent-based acrylic lacquer membraneforming curing and sealing compound. This material meets the requirements of ASTM C-309 and AASHTO M-148 for concrete curing.

The VOC content of this product is < 350 g/L when calculated to California Air Resources Board Architectural Coatings Program. Polyseal EZ uses alternative non-regulated solvents to meet reduced federal VOC requirements. Polyseal EZ does not meet the requirements of the South Coast Air Management District of less than 100 g/L VOC for concrete curing compounds. This would not qualify for EQ credit 4.1 Low Emitting Materials: Adhesives & Sealants, or 4.2 Low Emitting Materials: Paints and Coatings.

There are no recycled materials used to manufacture **Polyseal EZ**.

Polyseal EZ is manufactured at 300 Edwards Street, Madison, OH. 44057. If your project falls within a 500-mile radius or (Distance by rail/3) + (Distance by inland waterway/2) + (Distance by sea/15) + (Distance by all other means) ≤ 500 miles [800 kilometers] of this location; the product is considered a locally produced material and can help contribute to earning MR Credit 5.1: Regional Materials: 10% Extracted, Processed & Manufactured Regionally 1 Point, and MR Credit 5.2: Regional Materials: 20% Extracted, Processed & Manufactured Regionally 1 Point in addition to MR Credit 5.1.

ChemMasters products by virtue of being manufactured in United States are in compliance with the "Buy American Provision" set forth in the American recovery Reinvestment Act (ARRA) of 2009, section 1605.

John Kirk
ChemMasters Technical Service Manager
PH (440) 428-2105
PH (800) 486-7866
FAX (440) 428-7091
johnkirk@chemmasters.net
www.chemmasters.net