



# ChemMasters

## 1207 NON-METHYLENE CHLORIDE STRIPPER

SPECIALTY CONSTRUCTION PRODUCTS

### P R O D U C T      D A T A

#### DESCRIPTION

1207 Non-Methylene Chloride Stripper is a non-toxic, biodegradable sealer and coating stripper for concrete, masonry, wood and metal surfaces. This proprietary blend is extremely effective in removing aged curing and sealing compounds, acrylic or alkyd coatings, varnish and paint.

#### USES

- Exterior or interior, horizontal or vertical surfaces
- Suitable for use on concrete, masonry, wood and metal
- Removal of curing and sealing compounds, paints, varnish, acrylic or alkyd coatings
- Prepares surface for subsequent application of sealers or paints

#### ADVANTAGES

- Biodegradable, nontoxic alternative to standard MEK based compounds
- Pleasant citrus odor for interior applications
- Highly reactive for rapid removal of most common sealers
- Water rinsable, eliminates need for scraping by hand, saves time and labor costs
- Lifts build up of several layers in one application, excellent option for restoration projects

#### PACKAGING AND ESTIMATING GUIDE

1207 Non-Methylene Chloride Stripper is packaged in 5 U.S. gallon/18.7L steel pails, shipped 36 per pallet shrink wrapped.

Coverage is dependent upon thickness and type of material to be removed. For estimating purposes, the average coverage for a single application is 50 Ft.<sup>2</sup> per gallon/1.25 M<sup>2</sup> per liter.

#### TECHNICAL DATA

- Meets the requirements of the U.S.D.A. for use in federally inspected meat and poultry plants. Classification C-3 as a paint remover in non-processing areas

Color	Straw
Application Temperature	33°-95°F    1°-35°C
Fragrance	Citrus
Viscosity	200 cps
Flash Point	205°F/96°C C.O.C.
Freeze/Thaw Stability	3 cycles
Stability	2 years in unopened container

#### RECOMMENDED EQUIPMENT

- Solvent resistant lambs wool roller and rubber squeegee with long handles
- Eye protection with splash guards, impervious gloves and rubber boots are strongly advised
- Wire brush, stiff bristle broom or mechanical scrubber, wet/dry vacuum
- Metal drum or other steel container to hold spent residue for proper disposal

#### DIRECTIONS

Cover and protect any materials or equipment that might be damaged by contact. Remove any foodstuffs or materials which might absorb odors.

Surface Preparation: Surfaces to be treated must be free of any oil, grease, tar or other surface deposits. ChemMasters recommends the use of 1201 Citrus Cleaner Degreaser or 1202 Heavy Duty Cleaner/Degreaser to clean surfaces prior to applying 1207. Thoroughly wash and rinse surfaces as directed on individual data sheets, vacuum residue and allow surface to dry completely before beginning stripping operation.



## ChemMasters

An American Owned & Operated Company  
300 EDWARDS STREET • MADISON, OHIO 44057-3112  
(440) 428-2105 • FAX (440) 428-7091 • ORDER LINE: (800) 486-7866

Revised 11/13/98

YEL-22

**APPLICATION:** Apply a coat of 1207 Non-Methylene Chloride Stripper with a lambs wool applicator maintaining an approximate coverage rate of 50 Ft.<sup>2</sup> per gallon/1.25 M<sup>2</sup> per liter. For ease of application and removal, apply 1207 in narrow strips 3 feet/1 meter wide, not to exceed a comfortable reach with available tools.

Allow 1207 Non-Methylene Chloride Stripper to dwell on surface for 5-10 minutes. Do not allow material to dry on surface.

A visible wrinkling of the coating or sealer will be observed. When this pattern is uniform over entire treated surface, sprinkle with warm to hot water and begin scrubbing with wire brush or mechanical scrubber equipped with wire brushes to further loosen residue from surface.

Squeegee residue to side or vacuum and contain in metal drum, pail or other suitable container. 1207 Non-Methylene Chloride Stripper is not governed by any special disposal requirements but the substances removed from treated surfaces may contain controlled components. Consult project specifications or local EPA. before disposing of spent materials.

Any sealer, paint or coating remaining on surface after initial effort may be treated again for complete removal.

#### **CLEANUP**

Scrub treated surfaces with 1201 Citrus Cleaner Degreaser or 1202 Heavy Duty Cleaner/Degreaser diluted 10:1 with clean water. This final washing neutralizes any un-reacted stripper and removes any residue of sealer, coating or paint. Use a stiff bristle brush or mechanical scrubber for best results.

Allow surface to dry thoroughly prior to applying any subsequent coatings or sealers.

Clean tools and equipment before materials dry and harden with warm water and detergent. Mechanical removal may be necessary if materials have dried hard.

#### **STORAGE**

Store pails in cool, dry area away from sunlight and sources of heat. Shelf life of unopened containers is two years from date of manufacture.

#### **LIMITATIONS**

- Do not use in the presence of foodstuffs or other materials likely to absorb odor
- Cover and protect any materials or equipment that might be damaged by contact
- Always wear recommended protective clothing. Use a respirator when working in confined or inadequately ventilated areas
- Apply to thoroughly dry surfaces for optimum reactivity
- 1207 Non-Methylene Chloride Stripper is not governed by any special disposal requirements but the residue created in the removal process must be properly contained according to prevailing local and federal ordinances. Consult project specifications or local EPA. before disposing of spent materials.

#### **CAUTION**

Keep out of reach of children. Eye and skin irritant. Avoid contact with skin or eyes. Use with adequate ventilation. See Material Safety Data Sheet (MSDS) for comprehensive recommendations.

***This Product is Formulated and Labeled for Industrial and Commercial Use Only***

*FOR BEST RESULTS AND SAFEST USAGE, USER IS SPECIFICALLY DIRECTED TO CONSULT  
THE CURRENT MATERIAL SAFETY DATA SHEET AND PACKAGE LABEL FOR THIS PRODUCT*

*We warrant our products to meet our published specifications and to be free from defects in materials and workmanship to the acceptable quality levels defined in these specifications. If acceptable quality levels are not specified, the acceptable quality levels will be those normally supplied by us for the product. We make no guarantee of the results to be obtained from the use of our products. The determination as to the adaptability of any of our products to the specific needs of the Buyer is solely Buyer's prerogative and responsibility. We are glad to offer suggestions on the use of our products. Nevertheless, there are no warranties given except such expresses warranties offered in connection with the sale of a particular product. Our liability shall be limited to replacement of, or refund of an amount not to exceed the purchase price attributed to, the goods as to which such claim is made. Our selection of one of these alternatives shall be Buyer's exclusive remedy. IN NO CASE SHALL WE BE LIABLE FOR CONSEQUENTIAL OR SPECIAL DAMAGES, EVEN IF WE HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. THE FOREGOING WARRANTIES ARE IN LIEU OF ALL OTHER WARRANTIES, GUARANTEES, CO-CONDITIONS AND REPRESENTATIONS, EITHER EXPRESSED OR IMPLIED, WHETHER ARISING UNDER ANY STATUTE, COMMON LAW, USAGE OR TRADE, COURSE OF DEALING OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.*