



ChemMasters

SPECIALTY CONSTRUCTION PRODUCTS

POLYSEAL SOLVENT

THINNER AND EQUIPMENT CLEANER FOR SOLVENT
BASED CURING AND SEALING COMPOUNDS

P R O D U C T D A T A

DESCRIPTION

Polyseal Solvent is an especially blended hydrocarbon solvent compound that is highly reactive. It is used following application procedures as a cleaner and may be used to remove or thin solvent based membrane forming compounds.

USES

- Cleaning tools, equipment, solvent resistant sprayers
- Removing hydrocarbon based curing and sealing compounds from concrete and masonry
- Removal of over spray from various solvent resistant surfaces
- Dissolves SBR, styrene acrylate, acrylic or linseed oil resins
- Thins or cleans equipment used for Spray-Cure & Seal 25, Spray-Cure & Seal Plus, Polyseal, Anti-Spall 50 and Traz 25

TECHNICAL DATA

Flash Point	111°F	44°C
Odor	Aromatic hydrocarbon	
Specific Gravity	0.87	

PACKAGING

Polyseal Solvent is available in 5 gallon (18.9 Liter) pails or 1 gallon (3.7 Liter) pails packaged 4 per case.

APPLICATION

MEMBRANE REMOVAL: After a minimum of 28 days curing time, the Polyseal Solvent is applied over the curing membrane with a squeegee or solvent resistant sprayer at an undiluted rate of 100 Ft.² per gallon (2.5 M² per liter). Once uniformly applied, scrub the Polyseal Solvent into the sur-

face with a stiff bristle broom or power scrubber. Allow the Polyseal Solvent to dwell on the surface for approximately 10 minutes then repeat the scrubbing procedure. After the curing membrane dissolves, vacuum the residue, rinse with clean water and allow surface to dry thoroughly. If any curing membrane remains after the stripping operation, retreat area with the Polyseal Solvent following the process above.

It is important to remove residual curing membrane before applying any subsequent sealer, coating or penetrating treatment. Failure to thoroughly remove curing and sealing compounds or to rinse surface will result in adhesion, appearance or performance difficulties.

CLEANUP

If desired, use a citrus degreaser to remove any solvent film from equipment used to apply Polyseal Solvent.

LIMITATIONS

- Polyseal Solvent is not designed to remove epoxy coatings
- Polyseal Solvent is not recommended for removal of wax based curing membranes

STORAGE

Store tightly sealed containers away from direct sunlight or sources of heat. Polyseal Solvent will not freeze. Close container immediately after each use to avoid build up of moisture which may cause rusting of the container and discoloration of the material.

CAUTION

COMBUSTIBLE LIQUID: Keep away from heat or open flames. Use with adequate ventilation. May cause skin, eye or respiratory tract irritation. Do not take internally. Keep out of reach of children.



ChemMasters

An American Owned & Operated Company
300 EDWARDS STREET • MADISON, OHIO 44057-3112
(216) 428-2105 • FAX (216) 428-7091 • ORDER LINE: (800) 486-7866
www.chemmasters.net

Revised May 2002

This Product is Formulated and Labeled for Industrial and Commercial Use Only

*FOR BEST RESULTS AND SAFEST USAGE, USER IS SPECIFICALLY DIRECTED TO CONSULT
THE CURRENT MATERIAL SAFETY DATA SHEET AND PACKAGE LABEL FOR THIS PRODUCT*

We warrant our products to meet our published specifications and to be free from defects in materials and workmanship to the acceptable quality levels defined in these specifications. If acceptable quality levels are not specified, the acceptable quality levels will be those normally supplied by us for the product. We make no guarantee of the results to be obtained from the use of our products. The determination as to the adaptability of any of our products to the specific needs of the Buyer is solely Buyer's prerogative and responsibility. We are glad to offer suggestions on the use of our products. Nevertheless, there are no warranties given except such expresses warranties offered in connection with the sale of a particular product. Our liability shall be limited to replacement of, or refund of an amount not to exceed the purchase price attributed to, the goods as to which such claim is made. Our selection of one of these alternatives shall be Buyer's exclusive remedy. IN NO CASE SHALL WE BE LIABLE FOR CONSEQUENTIAL OR SPECIAL DAMAGES, EVEN IF WE HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. THE FOREGOING WARRANTIES ARE IN LIEU OF ALL OTHER WARRANTIES, GUARANTEES, CO-CONDITIONS AND REPRESENTATIONS, EITHER EXPRESSED OR IMPLIED, WHETHER ARISING UNDER ANY STATUTE, COMMON LAW, USAGE OR TRADE, COURSE OF DEALING OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.