



ChemMasters

SKID-DADDLE

RUBBER TIRE MARK REMOVER

SPECIALTY CONSTRUCTION PRODUCTS

P R O D U C T D A T A

DESCRIPTION

Skid-Daddle™ is a specially formulated cleaner designed for removal of rubber skid marks from epoxy or other polymer floor coating systems without harming the floor's surface. Skid-Daddle is a blend of special cleaning agents, surfactants and terpene solvents. It has a light amber color and a fresh citrus odor.

USES

- Interior or exterior, horizontal surfaces
- Steel trowelled concrete floors
- Surfaces coated with polymer coatings; epoxy, epoxy novalac, urethane, methyl methacrylate or vinyl ester coatings and toppings
- When diluted with water, use as a bucket cleaner or a machine cleaner to rid concrete floor or polymer floors of grease, dirt and oil

ADVANTAGES

- Cleans black marks associated with forklifts, skid steers and other wheeled devices without destroying the integrity of polymer coatings
- Neutral pH of 7 when mixed with water at all dilution rates, may be used on unsealed, plain concrete without fear of long term deterioration
- Pleasant, clean odor
- As part of regular maintenance procedures, deep cleans pores and capillaries of plain concrete preventing embedment of oil and grease
- Does not contain petroleum solvents

ESTIMATING GUIDE

Coverage of a cleaner is difficult to estimate due to extreme variables of surface texture and conditions. When diluted 1:1 with water, Skid-Daddle covers approximately 100 Ft.² per gallon/2.5 M² per liter.

PACKAGING

Skid-Daddle is available in 55 U.S. gallon/208 Liter drums and 5 U.S. gallon/18.9 Liter pails, shipped 36 per pallet shrink wrapped.

DIRECTIONS

ASA SPOT CLEANER ON RUBBER TIRE MARKS: Dilute Skid-Daddle 1:1 with water and spray or pour directly on the mark. Allow the solution to soften the tire mark for at least 15 minutes then scrub. Rinse well with clean water.

ASA BUCKET CLEANER: Dilute Skid-Daddle 10:1 with water.

IN AUTOMATIC SCRUBBERS: Dilute Skid-Daddle from 20:1 to 50:1 with water, depending on the amount of soil present.

Be sure to thoroughly rinse Skid-Daddle from the floor. More than one rinsing may be required to remove sudsy residue.

CLEANUP

Rinse tools and equipment with clean water.

STORAGE

Store tightly sealed containers in cool, dry area away from direct sunlight and sources of heat. Shelf life of properly stored material is at least one year from date of manufacture.

LIMITATIONS

- A test area is recommended. This is especially important if the exact chemistry of the floor sealer or coating is not known. Apply Skid-Daddle diluted 1:1 with water to a 1 Ft.²/0.33 M² area and scrub. If any deterioration of the coating or sealer is observed or if the surface loses its sheen, contact ChemMasters technical service department for alternate recommendations.

CAUTION

COMBUSTIBLE LIQUID: Keep away from heat or open flames. Use with adequate ventilation. May cause skin, eye or respiratory tract irritation. Do not take internally. Keep out of reach of children.



ChemMasters

An American Owned & Operated Company
300 EDWARDS STREET • MADISON, OHIO 44057-3112
(440) 428-2105 • FAX (440) 428-7091 • ORDER LINE: (800) 486-7866

Revised 11/13/98

YEL-8

This Product is Formulated and Labeled for Industrial and Commercial Use Only

***FOR BEST RESULTS AND SAFEST USAGE, USER IS SPECIFICALLY DIRECTED TO CONSULT
THE CURRENT MATERIAL SAFETY DATA SHEET AND PACKAGE LABEL FOR THIS PRODUCT***

We warrant our products to meet our published specifications and to be free from defects in materials and workmanship to the acceptable quality levels defined in these specifications. If acceptable quality levels are not specified, the acceptable quality levels will be those normally supplied by us for the product. We make no guarantee of the results to be obtained from the use of our products. The determination as to the adaptability of any of our products to the specific needs of the Buyer is solely Buyer's prerogative and responsibility. We are glad to offer suggestions on the use of our products. Nevertheless, there are no warranties given except such expresses warranties offered in connection with the sale of a particular product. Our liability shall be limited to replacement of, or refund of an amount not to exceed the purchase price attributed to, the goods as to which such claim is made. Our selection of one of these alternatives shall be Buyer's exclusive remedy. IN NO CASE SHALL WE BE LIABLE FOR CONSEQUENTIAL OR SPECIAL DAMAGES, EVEN IF WE HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. THE FOREGOING WARRANTIES ARE IN LIEU OF ALL OTHER WARRANTIES, GUARANTEES, CO-CONDITIONS AND REPRESENTATIONS, EITHER EXPRESSED OR IMPLIED, WHETHER ARISING UNDER ANY STATUTE, COMMON LAW, USAGE OR TRADE, COURSE OF DEALING OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.