



ChemMasters

SPECIALTY CONSTRUCTION PRODUCTS

SAFE-CURE 1200 CLEAR

CLEAR, CONCRETE CURING COMPOUND
MEETING ODOT SUPPLEMENTAL SPEC 800

P R O D U C T D A T A

DESCRIPTION

Safe-Cure 1200 Clear is a clear, water based, wax emulsion concrete curing compound for concrete. This formulation has been specifically designed to meet the Ohio Department of Transportation Supplemental Specification #800. When applied to fresh concrete, Safe-Cure 1200 creates a film over the concrete to retain water in the concrete to enable the cement to fully hydrate and thus allowing the concrete to achieve higher ultimate strength while reducing surface shrinkage cracks.

USES

• Safe-Cure 1200 Clear is used to cure any exterior concrete including pavement, curbing, sidewalks, driveways, parking lots, median barriers, and mat foundations.

ADVANTAGES

- D.O.T. approved in Ohio
- Stable solution to allow for reduced length and frequency of agitation
- Excellent moisture retention - consistently meets ASTM C309
- Superior spraying characteristics for economical application and reduced labor cost
- Available in pails, drums, bulk or totes

ESTIMATING GUIDE

Coverage is dependent on surface texture and porosity.

Curing	200 ft. ² /Gallon	5 M ² /Liter
--------	------------------------------	-------------------------

PACKAGING

Safe-Cure 1200 Clear is packaged in 5 gallon (18.9 liter) pails, shipped 36 per pallet, 55 gallon (208 liter) drums, 275 gallon (1040 liter) totes and bulk tanker loads containing up to 5,500 gallons (20,790 liters). ChemMasters also offers storage tanks for customers to use on large projects or at customer locations.

TECHNICAL DATA

- ASTM C-309, Types I Class A, *Standard Specification for Liquid Membrane-Forming Compounds for Curing Concrete*

- AASHTO M-148, Type I, Class A
- Complies with National Volatile Organic Compound Emission Standards for Architectural Coatings, Federal EPA Regulation 40 CFR Part 59
- Army Corps of Engineers CRD-C-300 Available Upon Request
- DOT Preapproved Material Available Upon Request for the state of Ohio

V.O.C. Content	30 gm/L
Water Loss	< 0.15 kg/m ² @ 24 hrs < 0.40 kg/m ² @ 72 hrs
Solids	25 +/- 2 %
Flash Point	NONE
Weight	8.42 lbs./gal. (1 Kg / L)

APPLICATION

MIXING: Do not dilute. Stir or agitate Safe-Cure 1200 Clear before using to disperse solids uniformly. If using a pump to recirculate Safe-Cure 1200 Clear, it is recommended that an air diaphragm pump be used. If using a centrifugal pump, mix only long enough to make the Safe-Cure 1200 Clear homogeneous. Do not over mix as this may cause foaming and may damage the curing compound.

APPLICATION: Use a low pressure, airless sprayer equipped with a fan tip or a short napped roller to apply. Hold sprayer tip 6-8 inches (15-20 cm) from the surface of concrete. Apply uniformly leaving no pinholes or gaps but avoid over applying or puddles.

CURING: Apply Safe-Cure 1200 Clear after all bleed water has dissipated and application will not mar surface.

DRYING TIME: Safe-Cure 1200 Clear dries in less than 4 hours at 70°F (21°C) at 50% relative humidity. Cooler temperatures or high relative humidity may slow drying process.



ChemMasters

An American Owned & Operated Company
300 EDWARDS STREET • MADISON, OHIO 44057-3112
(440) 428-2105 • FAX (440) 428-7091 • ORDER LINE: (800) 486-7866

March 2006

CLEAN-UP

Clean tools and equipment used in applying Safe-Cure 1200 Clear with warm water and detergent.

LIMITATIONS

- Safe-Cure 1200 Clear is not recommended for interior use or where appearance is important.
- Do not apply if surface or ambient temperature is below 40°F (4°C). Product should be conditioned to 50°F (10°C) prior to application.
- Do not use Safe-Cure 1200 Clear as a bond breaker for tilt-up construction.

STORAGE

Store in tightly closed containers in warm area, between 50°-100°F (10°-38°C). Do not allow to freeze. Shelf life of properly stored material is one year from date of manufacture.

CAUTIONS

May cause skin and eye irritation. Do not take internally. Keep out of reach of children.

All label precautions and the MSDS must be fully understood before using this product.

This Product is Formulated and Labeled for Industrial and Commercial Use Only

FOR BEST RESULTS AND SAFEST USAGE, USER IS SPECIFICALLY DIRECTED TO CONSULT THE CURRENT MATERIAL SAFETY DATA SHEET AND PACKAGE LABEL FOR THIS PRODUCT

We warrant our products to meet our published specifications and to be free from defects in materials and workmanship to the acceptable quality levels defined in these specifications. If acceptable quality levels are not specified, the acceptable quality levels will be those normally supplied by us for the product. We make no guarantee of the results to be obtained from the use of our products. The determination as to the adaptability of any of our products to the specific needs of the Buyer is solely Buyer's prerogative and responsibility. We are glad to offer suggestions on the use of our products. Nevertheless, there are no warranties given except such expresses warranties offered in connection with the sale of a particular product. Our liability shall be limited to replacement of, or refund of an amount not to exceed the purchase price attributed to, the goods as to which such claim is made. Our selection of one of these alternatives shall be Buyer's exclusive remedy. IN NO CASE SHALL WE BE LIABLE FOR CONSEQUENTIAL OR SPECIAL DAMAGES, EVEN IF WE HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. THE FOREGOING WARRANTIES ARE IN LIEU OF ALL OTHER WARRANTIES, GUARANTEES, CO-CONDITIONS AND REPRESENTATIONS, EITHER EXPRESSED OR IMPLIED, WHETHER ARISING UNDER ANY STATUTE, COMMON LAW, USAGE OR TRADE, COURSE OF DEALING OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.