

Date Prepared: 10/11/07
Supersedes: New
Product Name: Duraguard mMa Pigment Various Colors

ChemMasters

Material Safety Data Sheet

1. Chemical Product and Company Information

Product Name: Duraguard mMa Pigment Various Colors

ChemMasters
300 Edwards Street
Madison, Ohio 44057
440-428-2105

In Case of Emergency Contact:
CHEMTREC 800/424-9300

2. Composition / Information on Ingredients

Hazardous Components	CAS #	Exposure Limits		
		<u>OSHA(PEL/TWA)</u>	<u>ACGIH(TLV/TWA)</u>	<u>OTHER</u>
Carbon Black	1333-86-4	3.5 mg/m ³	None	---
Polyester Resin Pigment - NonHazardous	Mixture	NA	NA	---

3. Hazards Identification

CAUTION

May Cause eye, skin and lung irritation

Potential Health Hazards - Acute

Eye: May cause eye irritation. Direct contact with the liquid or exposure to its vapors may cause burning, tearing and redness.

Skin: May cause irritation. Prolonged or repeated exposure may cause redness and burning, drying and cracking of the skin and dermatitis. Persons with preexisting skin disorders may be more susceptible to the effects of this material.

Inhalation: Excessive concentrations of vapors or mists may cause irritation of the nose and throat and signs of nervous system depression. Persons with impaired lung function or asthma like conditions may experience additional breathing difficulties due to the irritating properties of this material.

Ingestion: Liquid is moderately toxic and may be harmful if swallowed.

Potential Health Effects - Chronic

Carbon Black is a possible Human Carcinogen by IARC but in paint or wet out form does not present a hazard.

Carcinogenicity:	NTP	IARC Monographs	OSHA Regulated
	NO	NO	NO

4. First Aid Measures

Eye: Immediately flush with plenty of clean water.

Skin: Remove contaminated clothing. Clean affected area(s) thoroughly with soap and water.

Inhalation: Remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.

Ingestion: Seek medical attention! Not a usual route of exposure.

SEEK MEDICAL ATTENTION IF SYMPTOMS PERSIST.

Date Prepared: 10/11/07
Supersedes: New
Product Name: Duraguard mMa Pigment Various Colors

5. Fire Fighting Measures

Flash Point (method used): 200°F (TCC with mixing))

Flammable Limits (% volume in air): **Lower** = NA **Upper** = NA

Auto Ignition Temperature: No data available

Extinguishing Media: Extinguish with water fog, dry chemical, CO2 or foam.

Hazard Combustion Products: Carbon dioxide, carbon monoxide and/or organic compounds

Fire Fighting Instructions: Do not enter confined fire space without full bunker gear including a positive pressure, NIOSH approved, self-contained breathing apparatus. Cool containers exposed to fire with water.

6. Accidental Release Measures

Spill: Shut off ignition sources. Absorb with inert material, then place in chemical waste container for later disposal.

7. Handling and Storage

Handling: Avoid inhalation of vapors and personal contact with product. Keep liquid away from heat, sparks and flame. Use with adequate ventilation. "Empty" containers can contain explosive vapors. Do not cut, drill, grind, weld or perform similar operations on or near containers. Do not pressurize drums to empty them.

Storage: Store containers tightly closed with adequate ventilation in a cool, dry area.

8. Exposure Controls / Personal Protection

Exposure Controls: Mechanical and local exhaust should be used for indoor use.

Personal Protection: Protective clothing, goggles, rubber gloves and a vapor respirator when TLV is exceeded.

9. Physical and Chemical Properties

Appearance: Various colors of medium viscosity

Odor: Solvent odor

Boiling Point: 260-295°F

Melting Point: Not applicable

Vapor Pressure (mm/Hg): NA

Vapor Density (Air = 1): NA

Solubility in Water: Negligible (<1%)

Specific Gravity (H2O = 1): 2.1

Evaporation Rate (n-Butyl Acetate = 1): NA

10. Stability and Reactivity

Chemical Stability: Stable

Conditions to Avoid: Heat, sparks and flame

Incompatibility (materials to avoid): Strong oxidizing agents. Strong acids, bases and select amines.

Hazardous Decomposition or By-products: Thermal decomposition in the presence of air may yield carbon monoxide, carbon dioxide and/or unidentified organic compounds.

Hazardous Polymerization: Will not occur

11. Toxicological Information

Components	Oral LD50 (rat)	Dermal LD50 (rabbit)	Inhalation LC50 (rat)
------------	-----------------	----------------------	-----------------------

No Information Available

Date Prepared: 10/11/07
Supersedes: New
Product Name: Duraguard mMa Pigment Various Colors

12. Ecological Information

No information Available.

13. Disposal Considerations

Dispose of in accordance with all federal, state, and local regulations. If uncertain of local requirements, contact the proper environmental authorities for information on waste disposal in your area.

14. Transportation Information

For U S National, International and Air Shipments:

Shipping Description: Not Regulated

Emergency Response Guide Number: NA

Hazard Class: NA

15. Regulatory Information

OSHA: This material is hazardous by definition of Hazardous Communications Standard (29 CFR 1910.1200)

CERCLA Reportable Quantity: 5000 pounds using Xylene (Benzene, DiMethyl)

SARA Title III:

Section 311/312 hazard categories: acute health, delayed health, fire

Section 313 reportable ingredients:

Components	CAS #	Maximum %
X		

16. Other Information

MSDS Status: New

Industrial Abbreviation Legend on page 4 of this MSDS.

Date Prepared: 10/11/07
 Supersedes: New
 Product Name: Duraguard mMa Pigment Various Colors

Industrial Abbreviation Legend

ACGIH	American Conference of Governmental Industrial Hygienists	mg/m ³	milligrams per cubic meter
CAA	Clean Air Act (EPA)	NIOSH	National Institute for Occupational Safety and Health
CERCLA	Comprehensive Environmental Response, Compensation & Liability Act of 1980 (Superfund) (EPA)	NTP	National Toxicology Program
CNS	Central Nervous System	OSHA	Occupational Safety and Health Administration
CWA	Clean Water Act (EPA)	PEL	Permissible Exposure Limit
DOT	Department of Transportation	ppm	parts per million
EPA	Environmental Protection Agency	RCRA	Resource Conservation and Recovery Act (EPA)
g/kg	grams per kilogram	SARA	EPA's Superfund Amendment and Reauthorization Act (EPA)
IARC	Internal Agency for Research on Cancer	STEL	Short-Term Exposure Limit, ACGIH terminology
LC50	Lethal Concentration in which 50% of the test animals are expected to die	TLV	Threshold Limit Value
LD50	Lethal Dose in which 50% of the test animals are expected to die	TWA	Time-Weighted Average

THIS PRODUCT IS FORMULATED AND LABELED FOR INDUSTRIAL AND COMMERCIAL APPLICATION ONLY

The information contained herein is given in good faith and based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. The Spray-Cure Company assumes no responsibility for personal injury or property damage to vendees, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of the material.