

Date Prepared: 3/31/09
Supersedes: 09/11/02
Product Name: Polyweld EXP Part A

ChemMasters

Material Safety Data Sheet

1. Chemical Product and Company Information

Product Name: Polyweld EPX Part A

Product Description:

ChemMasters
300 Edwards Street
Madison, Ohio 44057
440-428-2105

In Case of Emergency Contact:
CHEMTREC 800/424-9300

2. Hazards Identification

CAUTION

Causes Eye Irritation

Causes Skin Irritation and/or Allergic Skin Reaction

WHMIS Classification: Class D, Division 2B (Toxic)

Symbol: Stylized T

Potential Health Hazards - Acute

Eye: Irritant. May cause injury that persists for several days.

Skin: Sensitizer — may cause allergic reaction which can be severe in certain individuals. Moderately irritating.

Inhalation: Heating can generate vapors that may cause headaches, nausea, dizziness and respiratory irritation.

Ingestion: Slightly toxic. See Section 11.

Potential Health Effects - Chronic

Carcinogenicity:

NTP

NO

IARC Monographs

NO

OSHA Regulated

NO

3. Composition / Information on Ingredients

Hazardous Components	CAS #	Exposure Limits			% by Wt
		OSHA(PEL/TWA)	ACGIH (TLV/TWA)	OTHER	
Water	7732-18-5	NE	NE	---	40-45
Bisphenol-A Epoxy Resin	Proprietary	—	—	—	35-40
2-Propoxyethanol	2807-30-9	25 ppm Skin	25 ppm Skin	----	5-10
Aromatic Hydrocarbons	64742-95-6	NA	50 ppm	—	5
Diethylene Glycol Butyl Ether	112-34-5				5

Date Prepared: 3/31/09
Supersedes: 09/11/02
Product Name: Polyweld EXP Part A

4. First Aid Measures

Eye: Immediately flush with plenty of water for at least 15 minutes. Get medical attention.

Skin: Flush immediately with plenty of water for at least 15 minutes while removing contaminated clothing.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Ingestion: If appreciable quantities are swallowed, seek medical attention.

SEEK MEDICAL ATTENTION IF SYMPTOMS PERSIST.

5. Fire Fighting Measures

Flash Point (method used): >200°F (TCC)

Flammable Limits (% volume in air): **Lower** = No data available **Upper** = No data available

Auto Ignition Temperature: No data available

Extinguishing Media: Dry chemicals, CO₂, Halon, water spray or foam.

Hazard Combustion Products: Carbon dioxide and/or carbon monoxide.

Fire Fighting Instructions: Remove all ignition sources. Wear self contained breathing apparatus and complete personal protective equipment when entering confined areas where potential exposure to vapors or products of combustion exists.

6. Accidental Release Measures

Spill: Absorb with inert material, then place in chemical waste container for later disposal.

7. Handling and Storage

Handling: Use with adequate ventilation. Avoid contact with skin and eyes. Always use good industrial hygiene practices and safety guidelines when dealing with this potentially hazardous product.

Storage: Keep containers closed and store in a dry, well ventilated area.

8. Exposure Controls / Personal Protection

Exposure Controls: Mechanical exhaust should be used. A source of clean water should be available for flushing eyes and skin.

Personal Protection: Protective clothing, chemical splash goggles and rubber gloves.

9. Physical and Chemical Properties

Appearance: Light yellow liquid

Odor: Odorless

Boiling Point: No data available

Melting Point: Not applicable

Vapor Pressure (mm/Hg): <1

Vapor Density (Air = 1): >1

Solubility in Water: Soluble

Specific Gravity (H₂O = 1): 1.08

Evaporation Rate (n-Butyl Acetate = 1): No data available

Date Prepared: 3/31/09
Supersedes: 09/11/02
Product Name: Polyweld EXP Part A

10. Stability and Reactivity

Chemical Stability: Stable

Conditions to Avoid: Excessive heat

Incompatibility (materials to avoid): Contamination with strong acids, bases, amines and mercaptans.

Hazardous Decomposition or By-products: Thermal decomposition may yield carbon monoxide and/or dioxide.

Hazardous Polymerization: Will not occur

11. Toxicological Information

Components	Oral LD50 (rat)	Dermal LD50 (rabbit)	Inhalation LC50 (rat)
Bisphenol-A Epoxy Resin	2 g/kg	20 g/kg	—
Diethylene Glycol Butyl Ether	7292 mg/kg	2764 mg/kg	---
2-Propoxyethanol	---	870 mg/kg	>2000

12. Ecological Information

No data available

13. Disposal Considerations

Dispose of in accordance with all federal, state and local regulations. If uncertain of local regulations in your area, contact the proper environmental authorities for disposal.

This material does not meet RCRA's characteristic definition of ignitability, corrosivity, or reactivity, and is not listed in 40 CFR 261.33. The toxicity characteristic (TC), however has not been evaluated by the Toxicity Characteristic Leaching Procedure (TCLP).

14. Transportation Information

For U S National Shipments

Shipping Description: Non regulated

Emergency Response Guide Number: Not applicable

Hazard Class: Not applicable

15. Regulatory Information

OSHA: This material is hazardous by definition of Hazardous Communications Standard (29 CFR 1910.1200)

CERCLA Reportable Quantity: Not applicable

SARA Title III:

Section 311/312 hazard categories: acute health, delayed health

Section 313 reportable ingredients:

Components	CAS #	Maximum %
*2-Propoxyethanol	2807-30-9	7.5
*Diethylene Glycol Butyl Ether	12-34-5	5.0
1, 2, 4 Trimethylbenzene	95-63-6	1.6

*Glycol Ether Category

16. Other Information

MSDS Status: Revised March 31, 2009

Industrial Abbreviation Legend on page 4 of this MSDS.

Date Prepared: 3/31/09
Supersedes: 09/11/02
Product Name: Polyweld EXP Part A

Industrial Abbreviation Legend

ACGIH	American Conference of Governmental Industrial Hygienists	mg/m ³	milligrams per cubic meter
CAA	Clean Air Act (EPA)	NIOSH	National Institute for Occupational Safety and Health
CERCLA	Comprehensive Environmental Response, Compensation & Liability Act of 1980 (Superfund) (EPA)	NTP	National Toxicology Program
CNS	Central Nervous System	OSHA	Occupational Safety and Health Administration
CWA	Clean Water Act (EPA)	PEL	Permissible Exposure Limit
DOT	Department of Transportation	ppm	parts per million
EPA	Environmental Protection Agency	RCRA	Resource Conservation and Recovery Act (EPA)
g/kg	grams per kilogram	SARA	EPA's Superfund Amendment and Reauthorization Act (EPA)
IARC	Internal Agency for Research on Cancer	STEL	Short-Term Exposure Limit, ACGIH terminology
LC50	Lethal Concentration in which 50% of the test animals are expected to die	TLV	Threshold Limit Value
LD50	Lethal Dose in which 50% of the test animals are expected to die	TWA	Time-Weighted Average

THIS PRODUCT IS FORMULATED AND LABELED FOR INDUSTRIAL AND COMMERCIAL APPLICATION ONLY

The information contained herein is given in good faith and based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. ChemMasters assumes no responsibility for personal injury or property damage to vendees, users or third parties caused by the material.

Such vendees or users assume all risks associated with the use of the material.