

Date Prepared: 03/19/08
Supersedes: 10/29/07
Product Name: Release

ChemMasters

Material Safety Data Sheet

1. Chemical Product and Company Information

Product Name: Release

Product Description: Release is an oil and petroleum based form release agent with fragrance.

ChemMasters
300 Edwards Street
Madison, Ohio 44057
440-428-2105

In Case of Emergency Contact:
CHEMTREC 800/424-9300

2. Hazards Identification

CAUTION

COMBUSTIBLE LIQUID

Causes eye, skin and lung irritation

Harmful if inhaled

Harmful if swallowed

WHMIS Classification: Class D2B & B3 (Toxic & Flammable)

Symbol: Stylized T & Flammable

Potential Health Hazards - Acute

Eye: Causes eye irritation. Direct contact with the liquid or exposure to its vapors may cause burning, tearing and redness.

Skin: May cause irritation. Prolonged or repeated exposure may cause redness and burning, drying and cracking of the skin and dermatitis. Persons with preexisting skin disorders may be more susceptible to the effects of this material.

Inhalation: Excessive concentrations of vapors or mists may cause irritation of the nose and throat and signs of nervous system depression. Persons with impaired lung function or asthma like conditions may experience additional breathing difficulties due to the irritating properties of this material.

Ingestion: Liquid is moderately toxic and may be harmful if swallowed; may produce CNS depression. May result in vomiting. Aspiration of vomitus into the lungs must be avoided as even small quantities may result in aspiration pneumonia.

Potential Health Effects - Chronic

Kidney, lung and liver are probable target organs. See Section 11 for further information.

Carcinogenicity:	NTP	IARC Monographs	OSHA Regulated
	NO	2B	NO

This product may contain Naphthalene (91-20-3) & Ethyl Benzene (100-41-4) at concentrations above 0.1%. IARC has identified Naphthalene & Ethyl Benzene as possibly carcinogenic to humans (Group 2B) based on laboratory animal studies.

3. Composition / Information on Ingredients

Hazardous Components	CAS #	Exposure Limits		% by Wt	
		OSHA(PEL/TWA)	ACGIH (TLV/TWA)	OTHER	
Mineral Spirits as:					
Stoddard Solvent	8052-41-37	100 ppm	100 ppm	—	<30%
1,2,4, Trimethylbenzene	95-63-6	25 ppm	25 ppm	—	2%
1,3,5, Trimethylbenzene	108-67-8	25 ppm	25 ppm	—	2%
Mineral Oil	64741-89-5	5 mg/m ³	5 mg/m ³	—	65-70%
Fragrance	Proprietary				<1%

Date Prepared: 03/19/08
Supersedes: 10/29/07
Product Name: Release

4. First Aid Measures

Eye: Immediately flush with plenty of clean water.

Skin: Remove contaminated clothing. Clean affected area(s) thoroughly with soap and water.

Inhalation: Remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.

Ingestion: Seek medical attention! Do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs.

SEEK MEDICAL ATTENTION IF SYMPTOMS PERSIST.

5. Fire Fighting Measures

Flash Point (method used): 105°F (TCC)

Flammable Limits (% volume in air): **Lower** = 1 **Upper** = 6

Auto Ignition Temperature: No data available

Extinguishing Media: Extinguish with water fog, dry chemical, CO₂ or foam.

Hazard Combustion Products: Carbon dioxide and carbon monoxide.

Fire Fighting Instructions: Do not enter confined fire space without full bunker gear including a positive pressure, NIOSH approved, self-contained breathing apparatus. Cool containers exposed to fire with water.

6. Accidental Release Measures

Spill: Shut off ignition sources. Absorb with inert material, then place in chemical waste container for later disposal.

7. Handling and Storage

Handling: Avoid inhalation of vapors and personal contact with product. Keep liquid away from heat, sparks and flame. Use with adequate ventilation. "Empty" containers can contain explosive vapors. Do not cut, drill, grind, weld or perform similar operations on or near containers. Do not pressurize drums to empty them.

Storage: Store containers tightly closed with adequate ventilation in a cool, dry area.

8. Exposure Controls / Personal Protection

Exposure Controls: Not applicable — for outdoor use.

Personal Protection: Protective clothing, goggles, rubber gloves and a vapor respirator when TLV is exceeded.

9. Physical and Chemical Properties

Appearance: Amber liquid of low viscosity

Odor: Mineral spirits odor

VOC Content: 242 gm/L

Boiling Point: 327-413°F

Melting Point: Not applicable

Vapor Pressure (mm/Hg): 16 @ 100°F*

Vapor Density (Air = 1): 4.8*

Solubility in Water: Negligible (<5%)

Specific Gravity (H₂O = 1): 0.83

Evaporation Rate (n-Butyl Acetate = 1): <0.1* *estimated

10. Stability and Reactivity

Chemical Stability: Stable

Conditions to Avoid: Heat, sparks and flame

Incompatibility (materials to avoid): Strong oxidizing agents.

Hazardous Decomposition or By-products: Thermal decomposition in the presence of air may yield carbon monoxide and/or carbon dioxide.

Hazardous Polymerization: Will not occur

Date Prepared: 03/19/08
Supersedes: 10/29/07
Product Name: Release

11. Toxicological Information

Similar solvents when tested on rats by inhalation of vapors showed evidence of kidney, lung and liver damage.

Components	Oral LD50 (rat)	Dermal LD50 (rabbit)	Inhalation LC50 (rat)
Stoddard Solvent	>25 ml/kg	>3000mg/kg	>5.5mg/l
1,2,4, Trimethylbenzene	5 g/kg	—	>5500 ppm/m ³
1,3,5, Trimethylbenzene	5 g/kg	—	>5500ppm/m ³

12. Ecological Information

CWA considers petroleum distillates (Mineral Oil & Mineral Spirits) an oil under Section 311. Spills into or leading to surface waters that cause a sheen must be reported to the National Response Center.

13. Disposal Considerations

Dispose of in accordance with all federal, state, and local regulations. If uncertain of local requirements, contact the proper environmental authorities for information on waste disposal in your area.

Under RCRA 40 CFR 261 this material is hazardous waste number D001.

14. Transportation Information

For U S National Ground Shipments of \leq 119 gal containers: Not Regulated

For U S National Ground Shipments > 119 gal containers:

Shipping Description: Combustible Liquid, N.O.S. (Petroleum Distillates), Combustible Liquid, NA1993, III

Hazard Class: Combustible Liquid

For International and Air Shipping: Petroleum Distillates, N.O.S. (Mineral Spirits), 3, UN1268, III

Hazard Class: Flammable Liquid

Emergency Response Guide Number: 128

15. Regulatory Information

OSHA: This material is hazardous by definition of Hazardous Communications Standard (29 CFR 1910.1200)

CERCLA Reportable Quantity: The CWA considers petroleum distillates (Mineral Oil & Mineral Spirits) an oil under Section 311. Spills into or leading to surface waters that cause a sheen must be reported to the National Response Center.

SARA Title III:

Section 311/312 hazard categories: acute health, delayed health, fire

Section 313 reportable ingredients:

Components	CAS #	Maximum %
1,2,4 Trimethylbenzene	95-63-6	< 2 %
Xylene	1330-20-7	<.1%
Cumene	98-82-8	<.1%

California Proposition 65: This product may contain trace amounts of chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. Naphthalene (91-20-3) & Ethyl Benzene (100-41-4)

Date Prepared: 03/19/08
Supersedes: 10/29/07
Product Name: Release

15. Regulatory Information - Continued

New Jersey & Pennsylvania Right To Know:

1,2,4-Trimethyl benzene (95-63-6) <2%
Trimethyl benzene (25551-13-7) <2%
Cumene (98-82-8) <0.3%
Xylene, Mixed Isomers (1330-20-7) <0.2 %
n-Propyl benzene (103-65-1) <0.6%
Ethyl Benzene (100-41-4) <0.1%
Naphthalene (91-20-3) <0.01%

16. Other Information

MSDS Status: Revised MSDS March 19, 2008

Industrial Abbreviation Legend Below

Industrial Abbreviation Legend

ACGIH	American Conference of Governmental Industrial Hygienists	mg/m ³	milligrams per cubic meter
CAA	Clean Air Act (EPA)	NIOSH	National Institute for Occupational Safety and Health
CERCLA	Comprehensive Environmental Response, Compensation & Liability Act of 1980 (Superfund) (EPA)	NTP	National Toxicology Program
CNS	Central Nervous System	OSHA	Occupational Safety and Health Administration
CWA	Clean Water Act (EPA)	PEL	Permissible Exposure Limit
DOT	Department of Transportation	ppm	parts per million
EPA	Environmental Protection Agency	RCRA	Resource Conservation and Recovery Act (EPA)
g/kg	grams per kilogram	SARA	EPA's Superfund Amendment and Reauthorization Act (EPA)
IARC	Internal Agency for Research on Cancer	STEL	Short-Term Exposure Limit, ACGIH terminology
LC50	Lethal Concentration in which 50% of the test animals are expected to die	TLV	Threshold Limit Value
LD50	Lethal Dose in which 50% of the test animals are expected to die	TWA	Time-Weighted Average

THIS PRODUCT IS FORMULATED AND LABELED FOR INDUSTRIAL AND COMMERCIAL APPLICATION ONLY

The information contained herein is given in good faith and based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. The Spray-Cure Company assumes no responsibility for personal injury or property damage to vendees, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of the material.