

SAFETY DATA SHEET



Issue Date: June 6, 2017

Revision Date: June 25, 2018

Version 2017

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Graffiti Stopper, Part A Resin

Other Means of Identification:

SDS #: F1440A

Recommended Use: 2 Component Urethane Coating to Protect Concrete Surfaces from Graffiti

Restrictions on Use: No Data

Supplier of the Safety Data Sheet including Address:

ChemMasters Inc.
300 Edwards Street
Madison, OH 44057

Telephone Numbers

Company Phone Number: Phone: 800-486-7866, 440-428-2105
Fax: 440-428-7091

Emergency Telephone : ChemTrec 800-424-9300

2. HAZARDS IDENTIFICATION

Emergency Overview

OSHA Hazards

Flammable Liquid and Vapour, Causes eye, skin irritation, Harmful if swallowed or inhaled, May cause respiratory irritation, drowsiness or dizziness, May cause damage to kidneys, liver, brain and nervous system through prolonged and repeated exposure by inhalation.

GHS Classification

Flammable Liquids Category 3
Eye Irritation – Category 2B
Skin Corrosion/Irritation – Category 2
Acute Toxicity – Oral Category 4
Acute Toxicity – Inhalation Category 4
Specific Target Organ Toxicity – Single Exposure Category 3
Specific Target Organ Toxicity – Repeated Exposure Category 2

Label Elements, including precautionary statements

Pictograms: Three hazard pictograms in red diamond shapes: an exclamation mark, a person with a star on their chest, and a flame.

Signal Word: Warning

Hazard Statements:

- H226 Flammable Liquid and Vapour
- H302 Harmful if swallowed
- H320 Causes eye irritation
- H315 Causes skin irritation
- H332 Harmful if inhaled
- H335 May cause respiratory irritation
- H336 May cause drowsiness or dizziness
- H373 May cause damage to kidneys, liver, brain and nervous system through prolonged and repeated exposure by inhalation.

Precautionary Statement(s)

Prevention:

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- P233 Keep container tightly closed.
- P240 Ground and bond the container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting equipment.
- P242 Use non-sparking tools.
- P243 Take action to prevent static discharges.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P264 Wash skin thoroughly after handling
- P270 Do not eat, drink or smoke when using this product
- P271 Use only outdoors or in a well-ventilated area

Response:

- P301+P312+P330 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.
- P302+P352 IF ON SKIN: Wash with plenty of soap and water.
- P332+P313 If skin irritation occurs: Get medical advice/attention
- P362+P364 Take off contaminated clothing and wash before reuse
- P304+P340+P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P370+P378 In case of fire use, dry chemical, alcohol resistant foam, halon or carbon dioxide to extinguish.
- P314 Get medical advice/attention if you feel unwell.

- Storage:** P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P405 Store locked up.

Disposal: P501 Dispose of contents/container in accordance with local/regional/national regulations.

Hazards not otherwise classified: None Known

3. COMPOSITION/INFORMATION ON INGREDIENTS

Component

| | | |
|--|---------------------|--------|
| Polyester Resin Blend | CAS#: Not Available | 45-50% |
| 2-methoxy-1-methylethyl Acetate | CAS#: 108-65-6 | 30-35% |
| Silicone polyacrylate | CAS#: Not Available | 1-5% |
| Xylene | CAS#: 1330-20-7 | 1-5% |
| Ethyl Benzene | CAS#: 100-41-4 | 1-5% |
| Solvent Naphtha, Petroleum, Heavy Aromatic | CAS#: 64742-94-5 | 1-2% |

Ingredients not listed on this safety data sheet are considered to be non-hazardous according to OSHA 1910.1200 or are not present above their cutoff levels. Where a range is displayed, the exact percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First Aid Measures

General Advice: Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

Inhalation: IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

Eye Contact: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

Ingestion: IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth if conscious.

Skin Contact: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Wash off with soap and plenty of water. If skin irritation or rash occurs: Get medical advice/attention.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media: Alcohol-resistant foam, dry chemical, halon or carbon dioxide

Specific Hazards Arising from the Chemical

In a fire or if heated a pressure increase will occur and the container may burst.

Vapors are flammable and heavier than air. Vapors may travel across the ground and reach remote ignition sources causing a flashback fire danger.

Hazardous Combustion Products: Carbon oxides & Nitrogen oxides

Protective Equipment and Precautions for Firefighters

Wear self-contained breathing apparatus and full protective gear for firefighting.

Further Information: Use water spray to cool unopened containers. See Section 7 for safe handling and storage

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Use personal protective equipment. Avoid breathing dust/fume/gas/mist/vapours/spray. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental Precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains or waterways.

Methods and Material for Containment and Cleaning Up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations.

7. HANDLING AND STORAGE

Precautions for Safe Handling

Do not handle until all safety precautions have been read and understood. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond the container and receiving equipment. Take measures to prevent the buildup of electrostatic charge. Use non-sparking tools. Wash hands and skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Conditions for Safe Storage, Including any Incompatibilities

Keep container tightly closed in a dry, cool and well ventilated place.

Containers which are opened must be carefully resealed and kept upright to prevent leakage.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Component Exposure Limits

2-methoxy-1-methylethyl Acetate, CAS#: 108-65-6: TWA 50 ppm, AIHA.

Xylene, CAS#: 1330-20-7: TLV 100 ppm, ACGIH

Ethyl Benzene, CAS#: 100-41-4: TLV 100 ppm, ACGIH

Appropriate Engineering Controls

Local Ventilation: Recommended

General Ventilation: Recommended

Individual Protection Measures, such as Personal Protective Equipment

Eye/Face Protection: Use proper protection – Safety Glasses as a minimum

Skin and Body Protection: Wash at mealtime and end of shift. Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc.). Use chemical protective gloves as a minimum and wash skin promptly upon any skin contact.

Respiratory Protection: Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators.

General Hygiene Considerations: Handle in accordance with good industrial hygiene and safety practice. Wash hands before & after breaks and work day.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State: Liquid

Appearance: Clear

Color: Colourless

Odor: Solvent Odor

Odor threshold: No Data

Property

Vapor Pressure

Vapor Density

Relative Density

pH:

Melting/Freezing Point

Solubility

Evaporation Rate

Flash Point

Flammability Limits

Value

Not Available

Not Available

Not Available

Not Relevant

Not Relevant

Not Available

Not Available

42 Degrees C (107 Degrees F)

No Data

Remarks – Method

Setaflash Closed Cup

| | | |
|-------------------------------------|----------------------|------------------------|
| Flammability (Solid, gas) | Not Relevant | |
| Auto Ignition Temperature | Not Available | |
| Initial Boiling Point/Boiling Range | Not Available | |
| Decomposition Temperature | Not Available | |
| Viscosity | Not Available | |
| Specific Gravity | 1.06 at 25 Degrees C | 8.8 +/- 0.01 Lbs./gal. |

10. STABILITY AND REACTIVITY

Chemical Stability: Stable under recommended storage conditions

Possibility of Hazardous Reactions: Hazardous polymerization will not occur under recommended storage conditions

Conditions to Avoid: Heat, Flames and Sparks

Incompatible Materials: Keep away from oxidizing agents, reducing agents, peroxides and phosphorus compounds..

Hazardous Decomposition Products: Hazardous decomposition products formed under fire conditions, Carbon and Nitrogen oxides.

11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure: Inhalation, Skin Contact, Eye Contact
Ingestion is not a likely route of exposure under normal working conditions.

Symptoms of Exposure:

May cause allergic skin reaction, Causes serious eye irritation, May cause allergy or asthma symptoms or breathing difficulties if inhaled

Delayed and Immediate Effects as well as Chronic Effects from Short and Long-Term Exposure

Repeated Exposure may cause skin dryness and cracking.

Carcinogenicity:

Product is not expected to be carcinogenic.

Other Chronic Effects: None Known

Numerical Measures of Toxicity

2-methoxy-1-methylethyl Acetate: Oral LD50: Rat, 6,190 mg/kg; Dermal LD50: Rabbit, >5,000 mg/kg; Inhalation LC50 Rat 6 hrs. >4345 ppm

12. ECOLOGICAL INFORMATION

Ecotoxicity: Material may be toxic to aquatic organisms. .

Acute Toxicity: Fish

Components:

2-methoxy-1-methylethyl Acetate: LC50 Fathead Minnow, 96 hr, 161 mg/l

Acute Toxicity: Invertebrates

Components:

2-methoxy-1-methylethyl Acetate: EC50 Water Flea, 48 hr, 408 mg/l

Persistence and Degradability: Solvent portion is expected to be readily biodegradable.

Bioaccumulation: No Data Available

Mobility: This material has a low solubility in water. The solvent portion has high volatility (tendency to move from water to air) and will partition rapidly to the air. Therefore chronic aquatic toxicity is not expected, however a significant spill may cause long-term adverse effects in the aquatic environment.

Other Adverse Effects: No Data Available

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes: Under RCRA 40 CFR 261 this material is a hazardous waste. Dispose of in accordance with all federal, state, and local regulations. If uncertain of local requirements, contact the proper environmental authorities for information on waste disposal in your area. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated Packaging: Dispose of as unused product.

14. TRANSPORT INFORMATION

D.O.T.:

UN1263, PAINT, 3, III

Packaging Exception for 1 gal cans, 5 gallon pails & 55 gallon drums, *Ground Shipments Only.*

49 CFR 173.120(b)(2) A flammable liquid with a flash point at or above 38°C (100°F) that does not meet the definition of any other hazard class may be re-classed as a combustible liquid.

This product has a flash point at or above 38°C (100°F). It is therefore excepted from labeling requirements ..., specification packaging ..., and shipping papers... ***if shipped in non-bulk packaging. Non-bulk packaging*** means a packaging which has a maximum capacity of 450 Liters (119 gallons) or less as a receptacle for a liquid. Therefore, when shipped by ground in non-bulk packaging (≤ 119 gal.), this item is not DOT regulated.

This provision does not apply to transportation by vessel or air.

I.A.T.A.:

UN1263, PAINT, 3, III

I.M.D.G.:

UN1263, PAINT, 3, III

Marine Pollutant: No

15. REGULATORY INFORMATION

International Inventories

TSCA: All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

US Federal Regulations

SARA 302: CERCLA

Xylene RQ 100 lbs.

Ethyl Benzene RQ 1000 lbs.

SARA 311/312 Hazard Categories: Acute: Yes, Fire: Yes, Chronic: Yes

SARA 313 Hazard Categories:

| <u>CAS Number</u> | <u>Component Name</u> | <u>Wt. %</u> |
|-------------------|-----------------------|--------------|
| 1330-20-7 | Xylene | ≤ 4.6% |
| 100-41-4 | Ethyl Benzene | ≤ 3.3% |

SARA Extremely Hazardous Substances (EHS)/CERCLA hazardous Substances

CWA (Clean Water Act): This product contains organic solvents and may be subject to regulation by Section 311 of the Clean Water Act and the Oil Pollution Act. Releases of the product into or leading to surface waters must be reported to the National Response Center at 1-800-424-8802.

Supplemental State Compliance Information

California:

Warning: This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm. **Ethyl Benzene**

States Right To Know:

2-methoxy-1-methylethyl Acetate, CAS# 108-65-6: New Jersey, Pennsylvania

Xylene, CAS# 1330-20-7: New Jersey, Pennsylvania

Ethyl Benzene, CAS# 100-41-4: New Jersey, Pennsylvania

U.S. EPA Label Information: No Data

16. OTHER INFORMATION

HMIS Classification:

Health hazard: 2*

Flammability: 2

Physical Hazards: 0

NFPA Rating:

Health hazard: 2

Fire: 2

Reactivity Hazard: 0

Issuance Date: June 6, 2017

Revision Date: June 25, 2018

Revision Note: Reviewed and Updated

Date of Previous Version: October 31, 2014

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet