



ChemMasters®

Paver Enhancer™

Penetrating Treatment for Pavers
to Enhance Color &
Deepen Appearance

Quality • Innovation • Service

P R O D U C T D A T A

DESCRIPTION

Paver Enhancer is a penetrating, water-based treatment that deepens and enhances the color of architectural, interlocking, porous, dry cast pavers. This product was specifically designed for use on pavers for maximum cosmetic enhancement with excellent breathability. **Paver Enhancer** penetrates the surface of pavers, minimizing the formation of efflorescence and creating a matte finish that resists staining. **Paver Enhancer** is very low in Volatile Organic Compounds (V.O.C.) and compliant in the United States and Canada.

USES

- Exterior pavers to enhance, deepen, and enrich color development
- Enhance and protect the appearance of architectural dry cast pavers

ADVANTAGES

- Penetrating and fully breathable
- Will not contribute to the formation of efflorescence
- Helps maintain original appearance
- Resists staining from oil, grease, food, and beverages
- Protects pavers from water damage
- **Paver Enhancer** is a very low VOC emission product at <100 g/L V.O.C.
- Apply prior to glossy film forming sealers or over penetrating water proofers such as **Certi-Vex PowerSeal SS**

Packaging / Part Number		
4 x 1 gal (3.8L)	36/pallet	F1227.04
5 gal (18.9)	36/pallet	F1227.05

TECHNICAL DATA

Estimating Guide	
Varies with Surface Texture ft ² /gal (m ² /L)	
First coat	200 to 250 (4.9 to 6.1)
Optional 2nd coat	250 to 350 (6.1 to 8.5)

Test Data	
V.O.C.	< 100 g/L
Flash Point °F/°C (closed cup)	>212/100
Weight lbs/gal (kg/L)	8.42 (1.01)

Dry to Condition at 70°F and 50% relative humidity:	
To touch	2 to 4hrs
For foot traffic	4 to 6hrs
For wheeled traffic	24 hrs

DIRECTIONS

Surface Preparation:

- Apply only to porous dry cast pavers at least 60 days old or to older pavers previously sealed with **Paver Enhancer** or penetrating water proofers such as **Certi-Vex PowerSeal SS**. Age new pavers for 60 days to allow efflorescence to appear before application of **Paver Enhancer**. This is necessary to allow efflorescence removal before sealing in an undesirable appearance.



ChemMasters® Inc.

American Made Products—Family Owned Company

300 Edwards Street • Madison, OH 44057-3112 • PH: (440) 428-2105 • www.chemmasters.net

June 2024

- Thoroughly clean pavers using high pressure water and allow pavers to dry completely for at least 24 hours without precipitation, see paver manufacturer's recommendations.
- If efflorescence is present use diluted Muriatic Acid solution per paver supplier's recommendations.
- Always conduct a test application in an inconspicuous area to determine the finished appearance with **Paver Enhancer**.

Mixing: **Paver Enhancer** is packaged ready to use and only requires mild stirring or agitation prior to use. Do not dilute.

Application:

- Use a short nap roller and roller pan or a low pressure air less sprayer equipped with a fan nozzle. Hold sprayer tip 6 to 8 inches (15 to 20cm) from the surface.
- Apply uniformly leaving no pinholes or gaps. Do not allow to pool or puddle.
- An optional second coat may be applied, when surface is dry to foot traffic. To achieve the desired appearance always prepare a test area before applying to entire surface.
- Do not over apply.

Maintenance: Surfaces previously treated with **Paver Enhancer** should be cleaned and re-treated every 1 to 3 years depending on exposure and traffic when pavers no longer exhibit water repellency. Do not over apply.

Cleanup: Before material dries and hardens, clean tools and equipment with warm water and detergent.

Storage: Do not allow to freeze. Store tightly sealed containers in cool, dry area. Shelf life is one year from date of manufacture.

LIMITATIONS:

- **Paver Enhancer** is neither a sealer nor curing compound and should be used exclusively for cosmetic enhancement and improved stain resistance of pavers.
- **Paver Enhancer** is intended for use on new untreated (or previously treated with **Paver Enhancer** or **Certi-Vex PowerSeal SS**) porous dry-cast architectural or interlocking pavers only.
- Do not use if ambient or surface temperature is below 50°F (10°C). For best results, warm material to a minimum of 60°F (15.6°C) prior to application.
- Do not apply if rain is expected within 12 hours of application
- **Paver Enhancer** may highlight uneven color variations in pavers that may be most visible in light gray or beige colored pavers

CAUTIONS

- May cause skin, eye, and respiratory tract irritation.
- All label precautions, warranty, and Safety Data Sheet (SDS) must be fully understood before using this product.
- Make certain that the most current versions of the Product Data Sheet and SDS are being used. Go to www.chemmasters.net or contact ChemMasters Technical Service Department at 1.800.486.7866 to verify the most current version.
- Proper application is the responsibility of the user. ChemMasters can only make technical recommendations and cannot provide quality control on the jobsite. All label directions and the SDS must be understood before beginning application procedure.

**For professional use only
Keep out of reach of children**

THIS PRODUCT IS FOR COMMERCIAL USE ONLY – IT IS NOT A CONSUMER PRODUCT.

Before using this product read entirely this paragraph and the Manufacturer's Warranty and Limitations of Liability at Chem-Masters.net/Warranty.php (or by using the adjacent QR Code) incorporated herein (collectively the "Terms"). To reject any of the Terms buyer must return the unopened product container at once to the seller from which it was purchased. By opening or using this product buyer accepts without objection or modification all Terms. Subject to applicable law, **MANUFACTURER DISCLAIMS ALL IMPLIED WARRANTIES, INCLUDING IMPLIED WARRANTIES OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE**, and buyer agrees that in lieu of all other remedies in manufacturers sole discretion it will either replace defective product or refund the reasonable purchase price, and in no event may you recover from manufacturer any special, incidental or consequential damages even if it was aware of the possibility of such damages.

