

DIRECTIONS

Mixing: Do not dilute. **Silencure SRT** is packaged ready to use and only requires mild agitation or stirring before applying or filling equipment

Application:

For Best Results: Do not apply **Silencure SRT** if the temperature will drop below 50°F (10°C) within two hours of application. Protect people, vehicles, property, plants, windows, and all non masonry surfaces from product splash, residue, fumes, and wind drift.

Apply **Silencure SRT** after all bleed water has dissipated and within 2 hours of final finish. Applying **Silencure SRT** after two hours may result in poor penetration and lead to blotchiness, blistering and peeling. Do not apply over free standing water.

Apply uniformly leaving no pinholes or gaps. Do not allow the material to puddle.

Spray Apply: Use a low pressure, solvent resistant, airless sprayer equipped with a fan nozzle 0.50 to 1.0 gpm or a hand pressurized sprayer with a 'Cats Eye' nozzle (minimum orifice of 0.022 to 0.032") ensure spray equipment is clean and dry before adding **Silencure SRT**. The optimum spray pattern is an 8 to 12 inch fan. Hold sprayer tip 8 to 12 inches from the surface of the concrete.

Roller Apply: Use a short nap (1/4" max) solvent resistant roller. An optional second coat may be applied to a tack free surface at right angles to the first.

Formed Concrete Walls: If walls are not to receive further treatment, apply immediately after stripping forms or following rubbing operations at 450 ft²/gal (11m²/L).

CLEANUP

Clean tools and equipment used in applying **Silencure SRT** with warm water and detergent immediately after use.

STORAGE

Store tightly closed containers away from direct sunlight and sources of heat or flame. Shelf life is 1 year from date of manufacture.

LIMITATIONS

- **Silencure SRT** has an application window that begins when all bleed water has dissipated, extending to within 2 hrs of final finishing. If it cannot be completed within that window use a different film forming curing compound or wet cure the concrete.
- Not compatible with resilient floor covering adhesives and is not intended for use on surfaces to receive concrete overlays or toppings. Consult ChemMasters' Technical Service Department for compatibility with surface treatments. Always test for compatibility and adhesion.

- Solvent, gasoline, and hydraulic fluids must be cleaned quickly to prevent surface damage.
- Do not apply to joints or channels scheduled to receive elastomeric caulks.
- Do not use if ambient temperature is below 50°F (10°C). For best results condition material to a minimum of 60°F (15°C) prior to application. Application in cooler conditions will extend cure time and may impact final appearance.
- All label precautions and Safety Data Sheet must be fully understood before using.
- Protect adjoining glass, metal, or painted surfaces that may be etched or damaged by overspray or splash. Clean immediately with soap and water before drying. Use mineral spirits to remove dry material.
- Quality curing compounds may darken or highlight the subtle color variations naturally present in concrete.

Precautions:

WARNING: May be harmful if swallowed. Causes eye irritation. May be harmful if inhaled. May cause respiratory irritation.

Precautionary Statements: Avoid breathing dust/fume/gas/mist/vapours/spray. Wash hands and skin thoroughly after handling. Use only outdoors or in a well-ventilated area.

All label precautions and Safety Data Sheet must be fully understood before using.

**For professional use only.
Keep out of reach of children.**

THIS PRODUCT IS FOR COMMERCIAL USE ONLY – IT IS NOT A CONSUMER PRODUCT.

Before using this product read entirely this paragraph and the Manufacturer's Warranty and Limitations of Liability at Chem-Masters.net/Warranty.php (or by using the adjacent QR Code) incorporated herein (collectively the "Terms"). To reject any of the Terms buyer must return the unopened product container at once to the seller from which it was purchased. By opening or using this product buyer accepts without objection or modification all Terms. Subject to applicable law, **MANUFACTURER DISCLAIMS ALL IMPLIED WARRANTIES, INCLUDING IMPLIED WARRANTIES OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE**, and buyer agrees that in lieu of all other remedies in manufacturer's sole discretion it will either replace defective product or refund the reasonable purchase price, and in no event may you recover from manufacturer any special, incidental or consequential damages even if it was aware of the possibility of such damages.

©2024 ChemMasters

Printed in U.S.A.

