

Date Prepared: 09/22/08
Supersedes: 07/15/02
Product Name: ChemDeck Liquid

ChemMasters

Material Safety Data Sheet

1. Chemical Product and Company Information

Product Name: ChemDeck Liquid

ChemMasters
300 Edwards Street
Madison, Ohio 44057
440-428-2105

In Case of Emergency Contact:
CHEMTREC 800/424-9300

2. Hazards Identification

CAUTION
May Cause Eye Irritation

Potential Health Hazards - Acute

Eye: Direct contact may cause irritation.

Skin: Prolonged or repeated exposure may cause slight irritation.

Inhalation: Exposure to mist may cause headache, nausea and/or other symptoms of upper respiratory tract irritation.

Ingestion: Unlikely in hazardous amounts.

Potential Health Effects - Chronic:

None

Carcinogenicity:	NTP	IARC Monographs	OSHA Regulated
	NO	NO	NO

3. Composition / Information on Ingredients

Components	CAS #	Exposure Limits			% by Wt
		OSHA(PEL/TWA)	ACGIH (TLVTWA)	OTHER	
Acrylic Latex Emulsion	Proprietary	NE	NE	----	20-25
Water	7732-18-5	NE	NE	----	75-80

4. First Aid Measures

Eye: Immediately flush with plenty of water for 15 minutes.

Skin: Wash with soap and water.

Inhalation: Move victim to fresh air

Ingestion: If swallowed, give victim plenty of water. Consult a physician.

SEEK MEDICAL ATTENTION IF SYMPTOMS PERSIST.

5. Fire Fighting Measures

Flash Point (method used): Not applicable

Flammable Limits (% volume in air): Lower = Not applicable Upper =Not applicable

Auto Ignition Temperature: Not applicable

Extinguishing Media: Media appropriate for surrounding fire.

Hazard Combustion Products: Thermal decomposition may yield acrylic monomers.

Fire Fighting Instructions: Wear positive pressure, self-contained breathing apparatus.

Date Prepared: 09/22/08
Supersedes: 07/15/02
Product Name: ChemDeck Liquid

6. Accidental Release Measures

Spill: Contain spilled material by diking. Absorb with inert material, then place in chemical waste container for later disposal. Keep spills out of municipal sewers and open bodies of water.

7. Handling and Storage

Handling: Always use good industrial hygiene practices and safety guidelines.

Storage: Store material in its original container. Keep containers tightly closed when not in use. Protect from freezing.

8. Exposure Controls / Personal Protection

Exposure Controls: None required

Personal Protection: Safety glasses and rubber gloves should be worn to minimize contact with this material. A source of clean water should be available in work area for flushing eyes and skin.

9. Physical and Chemical Properties

Appearance: Milky white liquid of water consistency

Odor: Acrylic odor

Boiling Point: 212°F

Melting Point: Not applicable

Vapor Pressure (mm/Hg): 17 @20°C

Vapor Density (Air = 1): <1.0

Solubility in Water: 100%

Specific Gravity (H₂O = 1): 1.00

Evaporation Rate (n-Butyl Acetate = 1): <1.0

10. Stability and Reactivity

Chemical Stability: Stable under normal conditions

Conditions to Avoid: Freezing and temperatures above 340°F

Incompatibility (materials to avoid): None

Hazardous Decomposition or By-products: May yield acrylic monomers

Hazardous Polymerization: Will not occur

11. Toxicological Information

Components	Oral LD50 (rat)	Dermal LD50 (rabbit)	Inhalation LC50 (rat)
Not applicable	—	—	—

12. Ecological Information

Not toxic to fish or plants. Does not inhibit bacteria in waste treatment facilities. Polymer is not biodegradable. Product is not RCRA hazardous. The following information is based on analogy with a similar material. BOD (% Oxygen consumption) Day 20, 1-8%.

Date Prepared: 09/22/08
Supersedes: 07/15/02
Product Name: ChemDeck Liquid

13. Disposal Considerations

Dispose of in accordance with all federal, state, and local regulations. If uncertain of local requirements, contact the proper environmental authorities for disposal.

This material does not meet RCRA's characteristic definition of ignitability, corrosivity, or reactivity, and is not listed in 40 CFR 261.33. The toxicity characteristic (TC), however has not been evaluated by the Toxicity Characteristic Leaching procedure (TCLP).

14. Transportation Information

For U S National Shipments:

Shipping Description: Non-Regulated Material

Emergency Response Guide Number: Not applicable

Hazard Class: Not applicable

15. Regulatory Information

OSHA: This material is non-hazardous under the OSHA Hazard Communication Standard.

CERCLA Reportable Quantity: Not applicable

SARA Title III:

Section 311/312 hazard categories: Not applicable

Section 313 reportable ingredients:

Components	CAS #	Maximum %
Not applicable	—	—

16. Other Information

MSDS Status: Revised in accordance with GHS September 22, 2008

Industrial Abbreviation Legend on page 4 of this MSDS.

Date Prepared: 09/22/08
Supersedes: 07/15/02
Product Name: ChemDeck Liquid

Industrial Abbreviation Legend

ACGIH	American Conference of Governmental Industrial Hygienists	mg/m ³	milligrams per cubic meter
CAA	Clean Air Act (EPA)	NIOSH	National Institute for Occupational Safety and Health
CERCLA	Comprehensive Environmental Response, Compensation & Liability Act of 1980 (Superfund) (EPA)	NTP	National Toxicology Program
CNS	Central Nervous System	OSHA	Occupational Safety and Health Administration
CWA	Clean Water Act (EPA)	PEL	Permissible Exposure Limit
DOT	Department of Transportation	ppm	parts per million
EPA	Environmental Protection Agency	RCRA	Resource Conservation and Recovery Act (EPA)
g/kg	grams per kilogram	SARA	EPA's Superfund Amendment and Reauthorization Act (EPA)
IARC	Internal Agency for Research on Cancer	STEL	Short-Term Exposure Limit, ACGIH terminology
LC50	Lethal Concentration in which 50% of the test animals are expected to die	TLV	Threshold Limit Value
LD50	Lethal Dose in which 50% of the test animals are expected to die	TWA	Time-Weighted Average

THIS PRODUCT IS FORMULATED AND LABELED FOR INDUSTRIAL AND COMMERCIAL APPLICATION ONLY

The information contained herein is given in good faith and based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. ChemMasters assumes no responsibility for personal injury or property damage to vendees, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of the material.