



ChemMasters®

SPECIALTY CONSTRUCTION PRODUCTS

Polyseal Solvent

Thinner and Equipment Cleaner
for Solvent Based Curing and
Sealing Compounds

P R O D U C T D A T A

DESCRIPTION

Polyseal Solvent is a hydrocarbon solvent used following application procedures as a cleaner and may be used to thin solvent based membrane forming compounds depending on the local volatile organic compound (VOC) regulations.

USES

- Cleaning tools, equipment, solvent resistant sprayers
- Removal of over spray from various solvent resistant surfaces
- Cleans SBR, styrene acrylate, acrylic or linseed oil resins
- Thins or cleans equipment used for **Spray-Cure & Seal 25, Polyseal, Anti-Spall 55, Traz 25**, and other solvent-based acrylic products

Packaging Product Number		
5 gal (18.9L)	36 per pallet	F6502.05
1 gal (3.8L)	4 per case	F6502.04

TECHNICAL DATA

Test Data	
Flash Point °F (°C)	111 (44)
Odor	Aromatic hydrocarbon
Specific Gravity	0.87

Overspray Removal:

Use to clean overspray of solvent-based film forming acrylics from solvent resistant surfaces only. If the solvent resistance of a surface is unknown, test in a small inconspicuous area prior to use.

Spray **Polyseal Solvent** over contaminated surface and allow to dwell for approximately ten minutes, or until acrylic overspray can be removed with a **Polyseal Solvent** dampened cloth. Rinse surface thoroughly with clean water and allow to dry.

Tool/Equipment Cleaning:

Use to clean solvent resistant surfaces of jobsite equipment

and spray equipment used for application of solvent-based acrylics. Solvent resistant parts such as spray tips may be immersed in **Polyseal Solvent** to loosen and dissolve dried acrylics. Rinse thoroughly with clean water and allow to dry.

CLEANUP

If desired, use a citrus degreaser to remove any solvent film from equipment used to apply **Polyseal Solvent**.

LIMITATIONS

- **Polyseal Solvent** is not designed to remove epoxy coatings
- **Polyseal Solvent** is not recommended for removal of wax based curing membranes.
- Use outdoors only

STORAGE

Store tightly sealed containers away from direct sunlight or sources of heat. **Polyseal Solvent** will not freeze. Close container immediately after each use to avoid build up of moisture which may cause rusting of the container and discoloration of the material.

Precautions

Danger: Flammable Liquid and Vapor. Harmful if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects.

Precautionary Statements: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond the container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.



ChemMasters®

An American Owned & Operated Company
300 EDWARDS STREET • MADISON, OHIO 44057-3112 (440) 428-2105 • FAX (440) 428-7091 • ORDERLINE: (800) 486-7866 www.chemmasters.net

April 2018

This Product is Formulated and Labeled for Industrial and Commercial Use Only

FOR BEST RESULTS AND SAFEST USAGE, USER IS SPECIFICALLY DIRECTED TO CONSULT THE CURRENT PRODUCT & SAFETY DATA SHEETS AND PACKAGE LABEL FOR THIS PRODUCT. We warrant our products to meet our published specifications and to be free from defects in materials and workmanship to the acceptable quality levels defined in these specifications. If acceptable quality levels are not specified, the acceptable quality levels will be those normally supplied by us for the product. We make no guarantee of the results to be obtained from the use of our products. The determination as to the adaptability of any of our products to the specific needs of the Buyer is solely Buyer's prerogative and responsibility. We are glad to offer suggestions on the use of our products. Nevertheless, there are no warranties given except such expresses warranties offered in connection with the sale of a particular product. Our liability shall be limited to replacement of, or refund of an amount not to exceed the purchase price attributed to, the goods as to which such claim is made. Our selection of one of these alternatives shall be Buyer's exclusive remedy. IN NO CASE SHALL WE BE LIABLE FOR CONSEQUENTIAL OR SPECIAL DAMAGES, EVEN IF WE HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. THE FOREGOING WARRANTIES ARE IN LIEU OF ALL OTHER WARRANTIES, GUARANTEES, CO-CONDITIONS AND REPRESENTATIONS, EITHER EXPRESSED OR IMPLIED, WHETHER ARISING UNDER ANY STATUTE, COMMON LAW, USAGE OR TRADE, COURSE OF DEALING OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.